



JobStar steel western trains



Specifications:

Tri-Axle Trailer

20-cubic yards, no boards; 22.5-cubic yards with boards

Dimensions:

- 40 ft. overall length, 102-inch overall width
- 114-inch height w/o boards
- 193 x 90-inch hopper opening
- 111 x 55-inch gate opening
- Ground clearance under gate:
 - 17-inches w/ 24.5-inch tires
 - 16-inches w/ 22.5-inch tires

Pup Trailer

14-cubic yards, no boards, 16.5-cubic yards with boards

Dimensions:

- 24 ft. overall length, 102-inch overall width
- 114-inch height w/o boards, 193 x 90-inch hopper opening
- 111 x 55-inch gate opening
- Ground clearance under gate:
 - 17-inches w/24.5-inch tires
 - 16-inches w/22.5-inch tires

Trailer Bodies:

- 3/16-inch hopper skins throughout
- 79° hopper side slope, 55° hopper end slope, 90° slope lower hopper

- 4 x 6-inch bottom rail, 4 x 6-inch top rail and braces
- Rear fenders standard

Trailer Gates:

- 3/16-inch high tensile steel floor
- 8-inch externally mounted cylinders
- 80-gallon air tank in bottom rail
- Infinite gate positioning and feathering control
- Automatic injection air lubricator

Electrical:

- Sealed beam:** 7-way conduit in rubber grommets
- Separate gate circuit

Running gear:

- Axles:** 102-inch - 5-inch round 25K capacity
- Bearings:** Common inner and outer
- Suspension:**
 - Standard:** 44,000#, 4 spring - 3 leaf
 - Optional:** 50,000# single point
- Wheels:** 10-hole, hub piloted disc, 8.25 x 24.5
- Brakes:** 16-1/2 x 7-inch fast change
- Drums:** Outboard cast
- Tires:** 11R 24.5 radials
- ABS:** 2S - 1M standard

Paint: Premium epoxy primer. Urethane finish for excellent durability



Clement is just "down the road"
 Clement's nationwide network of dealers means that Clement quality service and genuine Clement replacement parts are just down the road not across the country.