



# JobStar steel western trains



## Specifications:

### Tri-Axle Trailer

20-cubic yards, no boards; 22.5-cubic yards with boards

### Dimensions:

- 40 ft. overall length, 102-inch overall width
- 114-inch height w/o boards
- 193 x 90-inch hopper opening
- 111 x 55-inch gate opening
- Ground clearance under gate:
  - 17-inches w/ 24.5-inch tires
  - 16-inches w/ 22.5-inch tires

### Pup Trailer

14-cubic yards, no boards, 16.5-cubic yards with boards

### Dimensions:

- 24 ft. overall length, 102-inch overall width
- 114-inch height w/o boards, 193 x 90-inch hopper opening
- 111 x 55-inch gate opening
- Ground clearance under gate:
  - 17-inches w/24.5-inch tires
  - 16-inches w/22.5-inch tires

### Trailer Bodies:

- 3/16-inch hopper skins throughout
- 79° hopper side slope, 55° hopper end slope, 90° slope lower hopper

- 4 x 6-inch bottom rail, 4 x 6-inch top rail and braces
- Rear fenders standard

### Trailer Gates:

- 3/16-inch high tensile steel floor
- 8-inch externally mounted cylinders
- 80-gallon air tank in bottom rail
- Infinite gate positioning and feathering control
- Automatic injection air lubricator

### Electrical:

- Sealed beam:** 7-way conduit in rubber grommets
- Separate gate circuit

### Running gear:

- Axles:** 102-inch - 5-inch round 25K capacity
- Bearings:** Common inner and outer
- Suspension:**
  - Standard:** 44,000#, 4 spring - 3 leaf
  - Optional:** 50,000# single point
- Wheels:** 10-hole, hub piloted disc, 8.25 x 24.5
- Brakes:** 16-1/2 x 7-inch fast change
- Drums:** Outboard cast
- Tires:** 11R 24.5 radials
- ABS:** 2S - 1M standard

**Paint:** Premium epoxy primer. Urethane finish for excellent durability



*Clement is just "down the road"*  
 Clement's nationwide network of dealers means that Clement quality service and genuine Clement replacement parts are just down the road not across the country.