



Two-axle, end dump, steel pup trailers



Specifications:

Chassis:

Frame: 4x8x3/16-inch reinforced with 1/2x3/8-inch flatbar

Drawbar: 3 cord truss (3x3x1/4-inch) spring ride hinged

Drawbar Eye: Rubber bushed

Suspension: 44,000 # 4-spring, 8-leaf

Axles: (2) 96-inch, 25,000 lb, 5-inch round pro par, common inner/outer bearings

Wheels: 8:25 x 24.5, 10-hole hub-piloted disc

Hubs: 10-Hole pilot hub

Tires: 11.00 x 24.5 Radial

Brakes: Air 16-1/2 x 7-inch cast drum

ABS: 2S 1M

Axle Spacing: 49-inch

Lights: 12 Volt sealed beam-rubber grommet

Wiring: Sealed harness, modular plug In

Mud Flaps: Rubber, rear only

Jack: On drawbar

Back Up Alarm: Yes

Rear Impact Guard: Yes

Body:

Type: Steel bathtub style dump for dirt, asphalt, or general construction work

Floor: 7-gauge HT50

Sides: 10-gauge HT50

Tailgate: 10-gauge HT50, top hinged air lock w/line to front

Front: 10 gauge HT50

Paint: One color urethane enamel over primed surface

Longitudinals: 4x6x3/16-inch tubing

Top Rail: 4x4x3/16-inch tubing

Side Braces: 10 gauge HT50 fabricated channel

Hoist Housing: None - under body hoist



Clement is just "down the road"

Clement's nationwide network of dealers means that Clement quality service and genuine Clement replacement parts are just down the road not across the country.