



"Michigan Trains" steel rock trailers



Specifications:

General Specifications

Semi

Chassis Frame: Fabricated hi-tensile steel I-beam, 18-inch main frame, 9-inch front section, 78-inch long, 42-1/2-inches wide

Suspension: 54,000-pound, # 6-spring, 3- leaf

Axles: (3) 102-inch, 25,000 pound, 5-inch round, common inner/outer bearings

Wheels: 8.25 x 22.5, 10-hole hub-piloted disc

Tires: 11 x 22.5 radial

Hubs: 10-hole, pilot hub

Brakes: Air, 16-1/2 x 7-inch outboard cast drum

ABS: 2S 1M

Axle Spacing: 44-inches

Lights: 12-volt sealed beam - rubber grommet

Wiring: Sealed harness modular plug-in

Mud Flaps: Rubber, rear only

Landing Gear: Stiff-leg standard

Back Up Alarm: Yes

King Pin Plate: 3/8-inch

Pintle Hook: Holland T-990

Air, lights & oil to rear tire carrier on semi

Body - Semi & Full

Type: Steel bathtub style body for sand, gravel, coal, hazardous waste, and aggregate

Floor: 7-gauge HT50

Sides: 10-gauge HT50

Tailgate: 10-gauge HT50, top hinged, air lock w/air line to front

Front: 10-gauge HT50

Paint: One color urethane enamel over primed surface

Longitudinals: 5 x 5 x 3/16-inch tubing

Top Rail: 4 x 4 x 3/16-inch tubing w/inverted angle

Side Braces: 10 12-gauge HT50

Hoist Housing: 10-gauge HT50

Steps: Inside & out

Spill Pan: 5-inch on semi

Full Chassis

Frame: Fabricated hi-tensile steel I-beam, 18-inch main frame, 9-inch front section, 78-inches long, 42-1/2-inches wide

Suspension: 44,000-pound, # 4-spring, 3-leaf to front, 54,000-pound # 6-spring, 3-leaf to rear

Axles: (5) 102-inch, 25,000-pound, 5-inch-round, common inner/outer bearings

Wheels: 8.25 x 22.5, 10-hole, hub-piloted disc

Tires: 11 x 22.5 radial

Hubs: 10-hole, pilot hub

Brakes: Air, 16-1/2 x 7-inch outboard cast drum

ABS: (2) - 1S 2M

Axle Spacing: 44-inches

Lights: 12-volt sealed beam - rubber grommet

Wiring: Sealed harness, modular plug in

Mud Flaps: Rubber, rear only

Back Up Alarm: Yes

Dolly Ring: Jost, 36-inch double race ball bearing

Drawbar: 60" heavy duty w/spring balance

Dolly Hinge: Rubber bushed

Push Bumper & Tow Hooks



P. O. Box 914, Minden, LA 71058-0914, 800-562-5948, www.clementind.com



Clement is just "down the road"

Clement's nationwide network of dealers means that Clement quality service and genuine Clement replacement parts are just down the road not across the country.